


# FIALab 2600 Series of Multi-Channel Analyzers

**FIALab**<sup>®</sup>

www.flowinjection.com

The FIALab-2600 Series are multi-channel analyzers for simultaneous determination of up to 4 parameters. FIALab 2600 (2-channel), FIALab 2630 (3-channel) and FIALab 2640 (4-channel) offer complete automation of wet chemical analysis for water, soil, plant tissue and manure as well as meat, dairy and other food products


The ease of use, robust design and adaptability make the FIALab 2600 series the best choice for environmental and agricultural laboratories.



FIALab-2600 2 channel analyzer

- Simultaneously determines nutrients including nitrate, phosphate and ammonia
- Wide detection range of spectrometer and broad spectrum of light source allow multiple wavelengths to be recorded simultaneously – extending the range of concentrations that can be evaluated in a single run
- Quantifies other environmental indicators such as sulfate, chloride and cyanide
- Pre-configured for in-line digestion and/or amperometric detection
- All methods are EPA compliant
- High reproducibility and accuracy
- Externally plumbed for ease of troubleshooting
- Standard configuration with Teledyne CETAC ASX-260 or ASX-520 autosampler
- Small footprint - Dual channel unit measures less than 18cm x 31cm x 33cm
- Low reagent consumption versus manual methods

## FIAlab for Windows Software



FIAlab for Windows is specifically designed to control the FIA series of analyzers. The software is easy to use for standard applications and versatile enough for use in numerous customized applications. For advanced users the software has a user friendly script-based programming language. The available commands are presented in a floating list box. The user simply points and clicks the desired command, automatically adding it to the procedure. FIAlab for Windows software features:

- Predefined methods
- Multiple wavelength selection for extended concentration range
- Program flexibility for custom applications
- Import sample registration file
- Report generation available in multiple formats and compatible with LIMS systems
- Concentration analysis can be calculated using peak height, area or slope
- Method development routines

## Agricultural and Environmental Assays

**Agricultural and Environmental Assays** are routinely performed with the FIALab-2600 series, including nitrate, nitrite, ammonia, phosphate, chloride and many others. The table lists a few methods, typical concentration ranges and sample throughputs. Additional methods for lower and higher concentration ranges, as well as for other analytes are available, please inquire. Some of the following methods can be performed with brackish/seawater samples.

Additional details of these assays are available on-line at:

Nitrate (Mid to High)	180 samples/hour	0.02 to 200 mg (N)/L	1 cm flow cell	Cadmium
Nitrite (Mid to High)	220 samples/hour	0.005 to 100 mg (N)/L	1 cm flow cell	
Nitrate (Low)	60 samples/hour	0.002 to 10 mg (N)/L	10 cm flow cell	Cadmium
Nitrite (Low)	80 samples/hour	0.0005 to 5 mg (N)/L	10 cm flow cell	
Nitrate (Ultra Low)	45 samples/hour	0.0004 to 1 mg (N)/L	50 cm flow cell	Cadmium
Nitrite (Ultra Low)	55 samples/hour	0.0001 to 0.5 mg (N)/L	50 cm flow cell	
Ammonia (Mid to High)	120 samples/hour	0.5 to 200 mg (N)/L	1 cm flow cell	Salicylate Method
Ammonia (Low)	80 samples/hour	0.01 to 10 mg (N)/L	10 cm flow cell	Salicylate Method
Ammonia (Ultra Low)	40 samples/hour	0.002 to 2 mg (N)/L	50 cm flow cell	Salicylate Method
Ammonia (Mid to High)	40 samples/hour	0.05 to 30 mg (N)/L	1 cm flow cell	Dialysis Cell
Ammonia (Low)	30 samples/hour	0.005 to 3 mg (N)/L	10 cm flow cell	Dialysis Cell
Ammonia (Ultra Low)	45 samples/hour	0.001 to 0.5 mg (N)/L	Fluorometric	OPA Method
TKN (Mid)	120 samples/hour	1.0 to 300 mg (N)/L	10 cm flow cell	Batch Digestion
Total Nitrogen	30 samples/hour	0.1 to 5 mg (N)/L	1 cm flow cell	In-line UV Digestion
Total Nitrogen	30 samples/hour	0.01 to 0.1 mg (N)/L	10 cm flow cell	In-line UV Digestion
Phosphate (Mid to High)	120 samples/hour	0.1 to 25 mg (P)/L	1 cm flow cell	Ortho/Bray/Olsen
Phosphate (Low)	60 samples/hour	0.01 to 2.5 mg (P)/L	10 cm flow cell	Ortho/Bray/Olsen
Phosphate (Ultra Low)	45 samples/hour	0.002 to 0.5 mg (P)/L	50 cm flow cell	Ortho
Fast Phosphate (Mid to High)	360 samples/hour	0.1 to 25 mg (P)/L	1 cm flow cell	Fast FIA Manifold
Fast Phosphate (Low)	240 samples/hour	0.01 to 2.5 mg (P)/L	10 cm flow cell	Fast FIA Manifold
Total Phosphorus (mid)	80 samples/hour	0.1 to 25 mg (P)/L	1 cm flow cell	
Total Phosphorus (low)	80 samples/hour	0.01 to 2.5 mg (P)/L	10 cm flow cell	
Chloride (Mid)	120 samples/hour	1 to 50 mg Cl-/L	1 cm flow cell	
Chloride (Low)	60 samples/hour	0.1 to 5 mg Cl-/L	10 cm flow cell	
Silica (Mid to High)	60 samples/hour	0.5 to 300 mg /L	1 cm flow cell	
Silica (Low)	60 samples/hour	0.05 to 30 mg /L	10 cm flow cell	
Silica (Ultra Low)	40 samples/hour	0.02 to 6 mg /L	50 cm flow cell	
Sulfate (Mid-high)	120 samples/hour	100 to 500 mg SO <sub>4</sub> /L	1 cm flow cell	
Sulfate (Low)	60 samples/hour	2 to 200 mg SO <sub>4</sub> /L	10 cm flow cell	
Iron (Mid)	140 samples/hour	0.025 to 100 mg/L	1 cm flow cell	
Iron (Low)	70 samples/hour	0.0025 to 10 mg/L	10 cm flow cell	
Iron (Ultra Low)	45 samples/hour	0.0005 to 0.2 mg/L	50 cm flow cell	

# The FIALab-2600 Series

## For automated routine testing of water, soil and food

The FIALab-2600 series of analyzers is designed to provide reproducible and consistent results every day – with speed, simplicity and cost efficiency.

The basic set-up consists of the FIALab-2600 analyzer, software, spectrometers, flow cells, light sources, fiber optics, tubing and connectors. The systems are used for automatic wet chemical analysis of nutrients and other parameters in water and soil as well as in meat, dairy and other food products. Accurate determination of nitrite, nitrate, ammonium, TKN, total nitrogen, phosphate and total phosphorus is done according to EPA-approved methods.

FIALab Instruments has been the leader and recognized innovator in the field of flow-based analytical techniques for over 25 years. Our instruments are used on all continents, including Antarctica. FIALab Instruments works closely with world leading research groups within the flow and sequential injection analysis community. Our new product and application development is at the cutting edge of our industry.

Every FIALab analyzer comes with a two-day training and installation package to make sure every customer masters their desired applications. You are guaranteed complete customer support through FIALab's 2-tier service contracts.

FIALab Instruments, Inc.  
14450 NE 29<sup>th</sup> Place, Suite 113  
Bellevue, WA 98007; USA  
Website: [www.flowinjection.com](http://www.flowinjection.com)  
Telephones: +1 425 376 0450  
                  +1 800 963 1101  
Fax: +1 425 376 0451  
Email: [sales@flowinjection.com](mailto:sales@flowinjection.com)  
          [support@flowinjection.com](mailto:support@flowinjection.com)

