

FIAlyzer-2000 Specifications

Analyzer	
Type:	Two-Channel Flow Injection Analyzer
Enclosure material:	Aluminum (powder-coated / anodized)
Peristaltic Pump	
Type:	10-channel peristaltic, common pressure plate
Materials:	Aluminum, stainless steel
Tubing type:	2-stop elastic tubing (Tygon, Pharmed etc)
Flow rate:	0.5-5.0 mL/min per channel (1.02 mm ID tubing) 0.3-2.8 mL/min per channel (0.76 mm ID tubing)
Valve	
Type:	12-port; Two Position Injection Valve
Wetted materials:	Plexiglas, Valcon E2 (proprietary reinforced PTFE composite)
Port type:	Flat-bottom ¼-28
Relay output	
Voltage:	24 V
Current:	Max 4mA
Dimensions	
Height:	11.5 in (29 cm)
Width:	7 in (18 cm)
Depth:	9.5 in (24 cm)
Weight:	18 lb (8 kg)
Communication	
Input:	USB
Output:	none
Control options:	FIAsoft software
Power requirements	
Voltage:	24 Vdc
Current:	Max. 2.5 A

FIALab Instruments, Inc.
 14450 NE 29th Place, Suite 113
 Bellevue, WA 98007 USA
 Website: www.flowinjection.com

Telephones: +1 425 376 0450
 +1 800 963 1101
 FAX: +1 425 376 0451
 Email: fiLAB@flowinjection.com